

## VESDA® by Concept

### VESDA—VLF250 LaserFOCUS™



#### Description

The **VESDA** LaserFOCUS detector is a very early warning smoke detector designed to protect small, business-critical environments of less than 250 m<sup>2</sup> (2500 sq. ft.).

The detector works by continually drawing air into sample holes in a pipe network. The air is filtered and passed into a detection chamber where light scattering technology detects the presence of very small amounts of smoke. Detector status information is communicated on the detector display and via relays or optional interface cards.

#### Application

The **VESDA** LaserFOCUS can be installed and commissioned out-of-the-box without the need for a special interface or software programming tools.

In operation, the unique Smoke Dial display provides the user with an instant understanding of a smoke event, even from a distance. Should a fault occur, the user simply opens the field service door and activates the Instant Fault Finder feature to determine the specific fault condition. This information can then be

passed onto their fire service company, ensuring that service technicians arrive onsite fully prepared.

**Ultrasonic Flow Sensing** The patent-pending Ultrasonic Flow Sensing used in the LaserFOCUS provides a direct reading of the sampling pipe flow rate. The system is immune to air temperature and pressure changes and is unaffected by contamination. **VESDA** is the first air sampling smoke detector to use ultrasonic flow sensing.

#### Features

- Out-of-the-Box Installation and Commissioning
- Ultrasonic Airflow Sensing
- Laser-Based Absolute Smoke Detection
- Pre-engineered pipe network designs
- Programmable Alarm Thresholds
- Dual Stage Air Filtration
- Instant Recognition Display
- Instant Fault Finder™
- AutoLearn™ Smoke
- AutoLearn™ Flow
- Field Service Access Door
- Multiple Event Logging in separate logs
- Event log – up to 18000 events
- Offline/online configuration capability
- Up to 250 m<sup>2</sup> (2500 sq. ft.) coverage

#### Listings/Approvals

- UL 268 listed
- UL 268A Duct listed
- FM approved
- FM approved for Hazardous Locations, Class I, Div. 2
- CCCf approved
- LPCB approved
- VdS approved
- VLF-250

Make **Concept** Fire Suppression Ltd and **VESDA** part of your fire protection plan.



## VESDA—VLF250 LaserFOCUS™

### Specifications

<b>Input Power</b>	
Voltage:	24V DC Nominal (18-30 V DC)
Current @ 24 VDC:	220 mA nominal, 295 mA in alarm
<b>Dimensions (W x H x D)</b>	255 mm x 185 mm x 90 mm (9 <sup>7</sup> / <sub>8</sub> in x 7 <sup>1</sup> / <sub>8</sub> in x 3 <sup>1</sup> / <sub>2</sub> in)
<b>Weight</b>	Approx. 2 kg (4.4 lbs)
<b>IP Rating</b>	IP30
<b>Mounting</b>	Upright, inverted or horizontal
<b>Operating Conditions†</b>	
Detector Ambient:	0 °C to 40 °C (32 °F to 104 °F)
Sampled Air:	0 °C to 40 °C (32 °F to 104 °F)
Humidity:	5% to 95% (non-condensing)
<b>Sampling Network</b>	
Maximum pipe lengths:	1 x 25 m (80 ft) (Max. 12 holes) 2 x 15 m (50 ft) per branch (Max. 6 holes per branch)
Sampling Hole Options:	Pre-Engineered Option or Maximum Pipe length in accordance with Pipe Modelling Design Tool (ASPIRE2™)

#### Air Inlet Pipe

Accepts both metric and American standard pipe sizes.  
Metric: 25 mm (1.05 in.) American Pipe: IPS 21 mm (¾ in.)

#### Area Coverage

Up to 250 m<sup>2</sup> (2500 sq. ft.) depending on local codes and standards

#### Relay Outputs

3 changeover relays (Fire 1, Action, Fault), Contacts rated 2A @ 30 VDC (max). NO/NC Contact

#### Cable Access

3 x 25 mm (1.05 in.) cable entries (1 rear entry, 2 top entry)

#### Cable Termination

Screw Terminals 0.2-2.5 mm<sup>2</sup> (30-12 AWG)

#### Interfaces

Shown in Terminal Block Connections diagram, to right, plus an RS232 Programming Port.  
General Purpose Input (GPI) interface offers: Reset, Disable, Standby, Alarm set 1, Alarm set 2 and External Input functions.

#### Alarm Threshold Setting Range

Alert, Action,	0.025 - 2.00% obs/m (0.008 - 0.625% obs/ft)
Fire 1, Fire 2	0.025 - 20.00% obs/m (0.008 - 6.25% obs/ft)
Individual Alarm Delays	0 – 60 seconds
Two Alarm Threshold Settings	Either time or GPI based

#### Display

- 4 Alarm State Indicators
- Smoke Level Indicator
- Reset, Disable and Test Controls
- Fault and Disabled Indicators
- Instant Fault Finder
- Smoke and Flow AutoLearn Controls

#### Event Log

Up to 18000 events, time and date stamped in separate, non-volatile, logs for: Smoke Level, Flow Level, Detector Status and Faults

#### AutoLearn Smoke & Flow

- Automatically set acceptable alarm thresholds for both smoke and flow levels
- Minimum 15 minutes, maximum 15 days (default 14 days)
- During AutoLearn thresholds are NOT changed from pre-set values

#### Warranty Period

2 years

#### Ordering Information:

VLF-250-00 VESDA LaserFOCUS. European language set. English display labels  
VLF-250-01 VESDA LaserFOCUS. European language set. International display labels  
VLF-250-02 VESDA LaserFOCUS. English + Asian language set. International display labels  
VIC-010 VESDAnet Interface Card  
VSP-005 Filter Cartridge  
VSP-715 Aspirator for VLF-250

### Display:

The display provided to the user includes a Smoke Dial and alarm and status indicators.



When the field service access door is open, the user has access to the RESET, DISABLE, Fire Test, AutoLearn and Instant Fault Finder functions. When the Instant Fault Finder function is activated, the Smoke Dial converts to a fault indicator, with the dial segment numbers corresponding to the faults listed below.

### Legend of fault indicators:

- |             |                       |
|-------------|-----------------------|
| 1 Filter    | 6 External Device/PSU |
| 2 Aspirator | 7 Interface card      |
| 3 High flow | 8 Field wiring        |
| 4 Low flow  | 9 AutoLearn Fail      |
| 5 n/a       | 10 Detector failure   |

### Terminal Block Connections:

1	GPI	
2	GPI	
3	Display TX	
4	Display RX	
5	Display Common Ground	
6	Display Power -	
7	Display Power +	
8	Power Return 0 VDC	From power supply unit
9	Power In 24 VDC	
10	Power Return 0 VDC	To next detector (if more than 1 detector per Power Supply Unit)
11	Power Out 24 VDC	
12	NC	
13	Common	Fault relay
14	NO	
15	NC	
16	Common	Action relay
17	NO	
18	NC	
19	Common	Fire 1 relay
20	NO	

VESDA and LaserFOCUS are registered trademarks of Xtralis AG.

Concept Fire Suppression Ltd  
Unit 4, The Stables, Newby Hall,  
Ripon, North Yorkshire,  
UK, HG4 5AE.  
Tel: +44 (0)1423 900883  
Fax: +44 (0)1423 301898

Concept Fire Suppression Ltd  
Hudson House, 8 Albany Street,  
Edinburgh, UK, EH1 3QB.  
Tel: +44 (0)131 516 7590  
Fax: +44 (0)131 473 2309

Concept Fire Suppression Ltd  
Albany House, 14 Shute End  
Wokingham, Berkshire,  
UK, RG40 1BJ.  
Tel: +44 (0)203 411 3212  
Fax: +44 (0)845 250 8101

Web: [www.conceptfire-uk.com](http://www.conceptfire-uk.com)  
E-mail: [info@conceptfire-uk.com](mailto:info@conceptfire-uk.com)