

VESDA® by Concept

VESDA—VLF250 LaserFOCUS™



Description

The **VESDA** LaserFOCUS detector is a very early warning smoke detector designed to protect small, business-critical environments of less than 250 m² (2500 sq. ft.).

The detector works by continually drawing air into sample holes in a pipe network. The air is filtered and passed into a detection chamber where light scattering technology detects the presence of very small amounts of smoke. Detector status information is communicated on the detector display and via relays or optional interface cards.

Application

The **VESDA** LaserFOCUS can be installed and commissioned out-of-the-box without the need for a special interface or software programming tools.

In operation, the unique Smoke Dial display provides the user with an instant understanding of a smoke event, even from a distance. Should a fault occur, the user simply opens the field service door and activates the Instant Fault Finder feature to determine the specific fault condition. This information can then be

passed onto their fire service company, ensuring that service technicians arrive onsite fully prepared.

Ultrasonic Flow Sensing The patent-pending Ultrasonic Flow Sensing used in the LaserFOCUS provides a direct reading of the sampling pipe flow rate. The system is immune to air temperature and pressure changes and is unaffected by contamination. **VESDA** is the first air sampling smoke detector to use ultrasonic flow sensing.

Features

- Out-of-the-Box Installation and Commissioning
- Ultrasonic Airflow Sensing
- Laser-Based Absolute Smoke Detection
- Pre-engineered pipe network designs
- Programmable Alarm Thresholds
- Dual Stage Air Filtration
- Instant Recognition Display
- Instant Fault Finder™
- AutoLearn™ Smoke
- AutoLearn™ Flow
- Field Service Access Door
- Multiple Event Logging in separate logs
- Event log – up to 18000 events
- Offline/online configuration capability
- Up to 250 m² (2500 sq. ft.) coverage

Listings/Approvals

- UL 268 listed
- UL 268A Duct listed
- FM approved
- FM approved for Hazardous Locations, Class I, Div. 2
- CCCf approved
- LPCB approved
- VdS approved
- VLF-250

Make **Concept** Gas Fire Suppression Ltd and **VESDA** part of your fire protection plan.



VESDA—VLF250 LaserFOCUS™

Specifications

Input Power	
Voltage:	24V DC Nominal (18-30 V DC)
Current @ 24 VDC:	220 mA nominal, 295 mA in alarm
Dimensions (W x H x D)	255 mm x 185 mm x 90 mm (9 ⁷ / ₈ in x 7 ¹ / ₈ in x 3 ¹ / ₂ in)
Weight	Approx. 2 kg (4.4 lbs)
IP Rating	IP30
Mounting	Upright, inverted or horizontal
Operating Conditions*	
Detector Ambient:	0 °C to 40 °C (32 °F to 104 °F)
Sampled Air:	0 °C to 40 °C (32 °F to 104 °F)
Humidity:	5% to 95% (non-condensing)
Sampling Network	
Maximum pipe lengths:	1 x 25 m (80 ft) (Max. 12 holes) 2 x 15 m (50 ft) per branch (Max. 6 holes per branch)
Sampling Hole Options:	Pre-Engineered Option or Maximum Pipe length in accordance with Pipe Modelling Design Tool (ASPIRE2™)

Air Inlet Pipe

Accepts both metric and American standard pipe sizes.
Metric: 25 mm (1.05 in.) American Pipe: IPS 21 mm (¾ in.)

Area Coverage

Up to 250 m² (2500 sq. ft.) depending on local codes and standards

Relay Outputs

3 changeover relays (Fire 1, Action, Fault), Contacts rated 2A @ 30 VDC (max). NO/NC Contact

Cable Access

3 x 25 mm (1.05 in.) cable entries (1 rear entry, 2 top entry)

Cable Termination

Screw Terminals 0.2-2.5 mm² (30-12 AWG)

Interfaces

Shown in Terminal Block Connections diagram, to right, plus an RS232 Programming Port.
General Purpose Input (GPI) interface offers: Reset, Disable, Standby, Alarm set 1, Alarm set 2 and External Input functions.

Alarm Threshold Setting Range

Alert, Action,	0.025 - 2.00% obs/m (0.008 - 0.625% obs/ft)
Fire 1, Fire 2	0.025 - 20.00% obs/m (0.008 - 6.25% obs/ft)
Individual Alarm Delays	0 – 60 seconds
Two Alarm Threshold Settings	Either time or GPI based

Display

- 4 Alarm State Indicators
- Smoke Level Indicator
- Reset, Disable and Test Controls
- Fault and Disabled Indicators
- Instant Fault Finder
- Smoke and Flow AutoLearn Controls

Event Log

Up to 18000 events, time and date stamped in separate, non-volatile, logs for: Smoke Level, Flow Level, Detector Status and Faults

AutoLearn Smoke & Flow

- Automatically set acceptable alarm thresholds for both smoke and flow levels
- Minimum 15 minutes, maximum 15 days (default 14 days)
- During AutoLearn thresholds are NOT changed from pre-set values

Warranty Period

2 years

Ordering Information:

VLF-250-00 VESDA LaserFOCUS. European language set. English display labels
VLF-250-01 VESDA LaserFOCUS. European language set. International display labels
VLF-250-02 VESDA LaserFOCUS. English + Asian language set. International display labels
VIC-010 VESDAnet Interface Card
VSP-005 Filter Cartridge
VSP-715 Aspirator for VLF-250

Display:

The display provided to the user includes a Smoke Dial and alarm and status indicators.




When the field service access door is open, the user has access to the RESET (power icon), DISABLE (square icon), Fire Test (flame icon), AutoLearn (diamond icon) and Instant Fault Finder functions. When the Instant Fault Finder function is activated, the Smoke Dial converts to a fault indicator, with the dial segment numbers corresponding to the faults listed below.

Legend of fault indicators:

- | | |
|-------------|-----------------------|
| 1 Filter | 6 External Device/PSU |
| 2 Aspirator | 7 Interface card |
| 3 High flow | 8 Field wiring |
| 4 Low flow | 9 AutoLearn Fail |
| 5 n/a | 10 Detector failure |

Terminal Block Connections:



VESDA and LaserFOCUS are registered trademarks of Xtralis AG.